

# XGSPON Bridge/Gateway

XGS-PON | 2.5Gigabit Ethernet | TR-069

## GRG-4285



**Comtrend's GRG-4285** is designed as an XGS-PON Bridge/Gateway with the capability to provide a strong and stable internet connection through XGS-PON fiber with one 2.5 Gigabit Ethernet port as LAN to connect with the wireless unit to provide seamless family internet access services.

The indoor models of Comtrend's xPON product line provide a lower cost and small package which contains many features including QoS, Data Bridge and multicast video support.

Compliant with standard OMCI definition, GRG-4285 is manageable from the remote side and supports the full range FCAPS functions including supervision, monitoring and maintenance.

### KEY FEATURES

- **XGS-PON: Symmetric 10G/10G UL/DL**, provides high speed fiber to the home services.
- **2.5 Gigabit Ethernet LAN port**: Capable of providing high-speed connectivity.
- **Routing Function**: Routing software function integrated.
- **Remote Management**: TR-069 standard data model for ISP remote control.

# GRG-4285

XGS-PON | 2.5Gigabit Ethernet | TR-069

## SPECIFICATIONS

HARDWARE SPECIFICATIONS	
Flash	NAND Flash: 128M Byte
RAM	DDR3: 256M Byte
Interfaces	XGS-PON (SC/APC) x 1 2.5 Gigabit Ethernet LAN x 1
LED Indicators	Power, Internet, PON, 2.5G ETH
Buttons	Reset button
Power Input	12VDC/1.5A
REMOTE MANAGEMENT	
Protocol	TR-069, HTTP, HTTPS, TELNET, SSH
CERTIFICATIONS	
CE	
PACKAGE CONTENTS	
XGS-PON Bridge/Gateway (GRG-4285) x 1	
Power adapter 12VDC/1.5A, 100-240VAC, 50/60Hz, 1.5m x 1	
RJ-45 Giga Ethernet cable (8P8C, 1.5m) x 1	
ENVIRONMENT	
Temperature	Operating: 0°C ~ 40°C (32°F ~104°F) Storage: -40°C ~ 70°C (-40°F ~158°F)
Humidity (Non-condensing)	Operating: 10 ~ 90% RH, non-condensing Storage: 5 ~ 90% RH, non-condensing



**Taiwan:**  
3F-1, No.10, Lane 609, Chongxin Road, Section 5,  
Sanzhong Dist, New Taipei City 241405, Taiwan  
Tel: +886-2-29998261

**USA & Canada:**  
530 Technology Dr. Suite 100, Irvine,  
CA 92618, USA  
Tel: +1-949-753-9640

**Spain:**  
[comercial@comtrend.com](mailto:comercial@comtrend.com)

**Czech Republic:**  
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,  
Czech Republic  
Tel: +420-266-782040

**India:**  
446 Sector 8, IMT Manesar, Gurugram,  
Haryana 122051, India  
E-mail: [india.admin@comtrend.com](mailto:india.admin@comtrend.com)

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.