

IP CAMERA

Outdoor Bullet Camera | IP66 | PoE 802.3af | 30fps @ 1920x1080

MB-21IR



The All-in-One Network Camera

Comtrend's MB-21IR Outdoor Bullet IP Camera is designed for the outdoor and is the ideal camera for reliable deployment in surveillance because of its all-in-one design and economic pricing. The MB-21IR is equipped with weather proof IP66 certified housing and has an anti-shear bracket to supply protection for hidden cables. The MB-21IR is designed for quick and flexible wall or ceiling mount installation with PoE capabilities and has built-in IR LEDs to support day/night function even in an environment with no light.

KEY BENEFITS

- **Ideal for Outdoor Use:**
The MB-21IR has IP66 weather proof certified casing and IR illuminators effective up to 65 feet.
- **Supports Multiple Video Streams:**
Can simultaneously stream H.264, MPEG-4, and MJPEG to provide both high-quality and bandwidth-efficient formats
- **Local Recording:**
Equipped with a MicroSD slot, video can be stored locally to ensure constant recording in case of a network interruption or failure.
- **Flexible Connectivity:**
The MB-21IR offers a PoE option for easy deployment in hard-to-reach locations.

MB-21IR

Outdoor Bullet Camera | IP66 | PoE 802.3af | Full HD



SPECIFICATIONS

Special Features

- Motion Detection: 3 Scalable Windows
- Privacy Mask: 3 Scalable Windows
- Recording Options: Remote Client, MicroSD Card or Remote Samba Recording
- Exposure Management: Full View/BLC (Metering Area), AWB, AES, AGC
- Image Settings: Brightness, Contrast, Sharpness, Saturation Adjustable
- Shutter Time: Auto/Menu Mode
- Mirror: Vertical, Horizontal
- Onvif Compliant: Support Onvif Profile S
- Digital Zoom: Up to 10x Digital Zoom
- Network Management: IP Filter, QoS (DSCP)
- Time Management: Manual Time Setting, Time Server & NTP Support, Real Time Clock
- User Access Control: Multi-Level User Access
- Multiple Streaming: Max. 3 Streams
- Configuration File: Backup to PC / Backup to SD card
- Language: Supports multiple languages

Event and Alarm Operation

- Alarm Trigger: Video Motion Detection, Digital Input (Always/Schedule setting)
- Event Action: FTP, Email, SD Card Rec., NAS Rec., Digital Output, One Snapshot/Rec. Video File.
- Alarm Rec. Buffer: 5 sec Pre-alarm / 5 sec post-alarm

Power Supply

- PoE / DC Power: PoE (IEEE802.3af), DC5V/2A
- Power Consumption: PoE, Max. 6W / DC5V, Max. 4.6W



Mechanical Spec

- Pan-n-Tilt: Pan: 360° / Tilt:70°
- Weatherproof: IP66

FEATURES

- Multi-stream from H.264/MPEG-4/MJPEG
- H.264 (30 fps @ 1920x1080)
- MPEG-4 (20 fps @ 1920x1080)
- IR illuminators, effective up to 65 feet
- Built-in MicroSD card slot (32GB max)
- IP66 weather proof
- Onvif Compliant (Profile S)
- PoE Power (IEEE802.3af)

DIMENSIONS



COMTREND CORPORATION

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sancong Dist, New Taipei City 24159, Taiwan
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

USA & Canada:
14 Chrysler, Irvine CA 92618, USA
Tel: 1-949-7539640
Fax: 1-949-7539020

Spain:
Edif. América II C/Prócion,7 portal 3 bajo H 28023
Madrid, Spain
Tel: 34-917990403
Fax: 34-913510999

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990