

PoE-9213

GIGABIT | POWER OVER ETHERNET (PoE) EXTENDER

PRODUCT OVERVIEW

Comtrend's PoE-9213 Power over Ethernet (PoE) Extender easily extends a PoE network connection to a remote location. It auto-detects a PoE (15.4 Watts) or PoE+ (30 Watts) signal and extends it an additional 328ft(100M) for a total distance of up to 656ft (200M) from the PoE device. Daisy chain two extenders for a non-powered total network length of 980ft (300M). With a wall-mountable option, the PoE-9213 offers simplified, flexible network planning.



KEY BENEFITS

Extends Power to Far Away Locations

Power a remote PoE device as far away as 656ft (200M) in locations where power is not readily accessible.

Reduces Installation Time & Costs

Eliminates the need to install high voltage outlets and electrical cabling.

Reliable, Flexible Power Supply

Supports 802.3af, ensuring compatibility with other 802.3af PoE Switches or PoE Injectors. It also features PoE short circuit protection to safeguard network devices.

Easy Setup

Plug and play desktop or wall-mounted installation.

PoE-9213

Easily Extends Power + Data to Remote PoE Devices

Front:



PoE Out:

Use this port to plug in your PoE-Enabled Device

Back:



PoE In:

Use this port to plug in a PoE Switch or PoE Injector

PoE Switch/PoE Injector



PoE Extender



PoE-Enabled Device

328ft (100M)

328ft (100M)

Total Distance: 656ft (200M)

SPECIFICATIONS

Hardware
<ul style="list-style-type: none">2 x 10/100/1000Mbps Ethernet LAN Ports<ul style="list-style-type: none">1 PoE IN Port1 PoE OUT Port
Standards
<ul style="list-style-type: none">IEEE 802.3 10BaseTIEEE 802.3u 100BaseTXIEEE 802.3azIEEE 802.3at, IEEE 802.3af
Case
<ul style="list-style-type: none">Metal
Input Power
<ul style="list-style-type: none">802.3af PoE Switch or PoE Injector

Environmental Conditions
<ul style="list-style-type: none">Operating Temperature: 32~104°F (0~40°C)Storage Temperature: -40 ~158°F (-40~70°C)Operating Humidity: 10~90% RH (Non-Condensing)Storage Humidity: 5~90% RH (Non-Condensing)
Certifications
<ul style="list-style-type: none">CE, FCC
Package Contents
<ul style="list-style-type: none">PoE ExtenderQuick Installation Guide
Dimensions
<ul style="list-style-type: none">3.15in x 3.40in x 1.00in (L x W x H)80mm x 86mm x 25mm (L x W x H)
Note: Specifications are subject to change without notice.

DS_PoE-9213_V1.0.1

Comtrend | www.comtrend.com | 14 Chrysler, Irvine CA 92618 | (877) 266-8736