

Wi-Fi Router AX3000

802.11ax | GE LAN | GE WAN | VoIP | TR-069

VG-8032



VG-8032 is equipped with a dual core processor, operates at a main frequency of 1.0GHz and provides superior processing speed and stable operation.

2.4G and 5G support the new generation Wi-Fi 6 (11ax) standard, having stronger anti-interference capability and faster transmission rate. The dual frequency concurrent wireless rate is up to 3000Mbps. Furthermore, VG-8032 provides one WAN + three LAN full gigabit network ports, convenient for home networking.

KEY FEATURES

- Supports Wi-Fi 6 (802.11ax) new generation Wi-Fi standard
- Supports 2.4GHz, 5GHz, dual frequency concurrently, automatically selecting 2.4G or 5G frequency band
- 2.4G supports 40MHz bandwidth, and 5G supports 160MHz bandwidth
- Supports BSS coloring which makes more use of the Wi-Fi spectrum by reducing interference to ensure more efficient service to multiple connected devices in busy Wi-Fi environments
- OFDMA and MU-MIMO support up-link and down-link, allows efficient data transmission for more devices at the same time
- Supports mesh networking; say goodbye to cumbersome wiring, realize automatic networking and whole home Wi-Fi 6 coverage
- Provides a full Gigabit WAN port and three full Gigabit LAN ports
- Supports Voice over Internet Protocol (VoIP) as a flexible and affordable solution for voice services

VG-8032

802.11ax | GE LAN | GE WAN | VoIP | TR-069

SPECIFICATIONS

Main Chipset	- Flash Memory: 128MB - SDRAM: 256MB
Interface	- Ethernet LAN: 3x RJ-45 Port (Yellow color, unshielded) 10/100/1000Mbps - WAN: 1x RJ-45 GE WAN - VoIP: 1x RJ-11 FXS - USB: 1x USB2.0 - WLAN: 2.4G 11ax 2T2R+5G 11ax 2T3R, 5x internal antennas - Buttons: 1x Reset/WPS button - MESH: 1x MESH button - Power Jack: DC power jack - Switch: On/Off switch
Power	- Adaptor Input: 100 ~ 240 VAC(±10%), 50/60Hz - Adaptor Output: Single-output-DC 12V, 1.5A
ENVIRONMENT	
Physical & Environmental	- Operating Temperature: 0 °C ~40 °C (32 °F ~104 °F); - Storage Temperature: -20 °C ~70 °C (-4 °F ~158 °F) - Operating Humidity: 0 to 95% RH - Storage Humidity: 0 to 95% RH
Green Product Requirement	RoHS

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanchong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

India:
446 Sector 8, IMT Manesar, Gurugram,
Haryana 122051, India
E-mail: india.admin@comtrend.com

USA & Canada:
530 Technology Dr. Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
comercial@comtrend.com

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.