

Home Gateway

VDSL(17a) | Fast Ethernet Port

VR-3034 VDSL Router



The VR-3034 is one Fast Ethernet ports router compliant Multi-DSL router that supports both ADSL2+ and VDSL2.

VDSL2 is a brand new standard and technology perfect for triple play (Video, Voice and Data) applications. The VR-3034 comes with one 10/100 Base-T Ethernet ports.

The VR-3034 is a cost effective solution designed to meet the needs of ISPs and carriers planning on deploying a single DSL device for covering end users in different loop range areas. Deploying VR-3034 is cost effective for ISPs and carriers because deploying a single CPE DSL device with multiple profile support minimizes the number of required upgrades.




VR-3034 VDSL Router

VDSL(17a) | Fast Ethernet Port

Features

- Automatically switches to ADSL2+/VDSL2 according to the port setting of DSLAM
- Up to VDSL2 17a Profile
- US0
- PhyR and G.INP, G.Vector
- Up to 16 PVCs and Up to 8 PTM flows
- Auto WAN detection
- IPv6 compliant
- UPnP
- IGMP Snooping/Proxy and Fast Leave
- DNS Proxy/Relay
- DHCP Server/Client
- Dynamic IP assignment
- NAT/PAT
- IP/MAC address filtering
- Static route and RIP/RIP v2 routing function
- Packet level QoS
- Embedded SNMPv2 agent
- Telnet/SSH/FTP/TFTP server
- TR-064/TR-069/TR-098/TR-111
- TR-069 compliant with Comtrend ACS
- Configuration backup and restoration
- Web-based management (HTTPS/HTTP)
- Remote administration, automatic firmware upgrade and configuration



VR-3034 VDSL Router

VDSL(17a) | Fast Ethernet Port

Specification

Hardware

- RJ-11 X1 for VDSL2/ADSL2+ (Annex A)
- RJ-45 X 1 for Fast Ethernet LAN
- Reset button X 1
- Power switch X 1

ADSL

- G.994
- G.992.1 (G.dmt) Annexes A
- G.992.2 (G.lite) Annexes A
- ANSI T1.413
- G.992.3 (ADSL2) Annexes A
- G.992.5 (ADSL2+) Annexes A

VDSL

- G.993.2(VDSL2) 17a, 12a, 12b, 8a, 8b, 8c, 8d
- G.993.5 (G.vector)
- G.998.4 (G.INP)
- SRA (Seamless Rate Adaptation)
- UPBO (Upstream Power Back-off)

Ethernet

- IEEE 802.3i, IEEE 802.3u
- 10BASE-T
- 100 BASE-TX,
- Auto-sense
- Support MDI/MDX

Networking Protocols

- RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Router, RFC 2516 (PPPoE); RFC 1577 (IPoA)
- PPPoE Pass-Through, Multiple PPPoE Sessions on Single WAN Interface
- PPPoE Filtering of Non-PPPoE Packets Between WAN and LAN
- Transparent Bridging Between all LAN and WAN Interfaces
- 802.1p/802.1q VLAN, DSCP
- IGMP Proxy V1/V2/V3, IGMP Snooping V1/V2/V3, Fast leave
- Static route, RIP v1/v2, ARP, RARP, SNTP
- DHCP Server/Client/Relay, DNS Proxy/ Relay, Dynamic DNS, UPnP, DLNA
- IPv6 Dual Stack, IPv6 Rapid Deployment (6RD)

Management

- TR-069/TR-098/TR-104/TR-111/TR-181, SNMP, Telnet, Web- Based Management, Configuration Backup and Restoration
- Software Upgrade via HTTP, TFTP Server, or FTP Server

Firewall/Filtering

- Stateful Packet Inspection Firewall
- Stateless Packet Filter
- URI/URL Filtering
- Denial of Service (DOS): ARP Attacks, Ping Attacks, Ping of Death, LAND, SYNC, Smurf, Unreachable, Teardrop
- Port Scan Detection and Protection
- TCP/IP/Port/Interface Filtering Rules Support Both Incoming and Outgoing Filtering

NAT/PAT

- Support One to One, Many to One, Many to Many (Overload), Many to Many (No Overload) NAT
- NAT Loopback
- Port Triggering
- Port Forwarding (Virtual Server)
- Symmetric port-overloading NAT, Full-Cone NAT
- DMZ host
- VPN Pass Through (PPTP, L2TP, IPSec)

Power Supply

- External power adapter: 12VDC/ 1.0A

Environment

- Operating Temperature: 0°C ~40°C (32°F ~104°F)
- Operating Humidity: 10%~90% non-condensing
- Storage Temperature: -25°C ~65°C (-23°F ~149°F)
- Storage Humidity: 5%~90% non-condensing

Dimension

- 171 x 122 x 38mm (WxDxH)

Weight

- 0.6 kg

COMTREND

Taiwan

3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanchong Dist, New Taipei City 24159, Taiwan
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

Spain

Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid,
Spain
Tel: 34-917990403
Fax: 34-913510999

Czech Republic

TOKOVO Jankovcova 1518/2, 170 00, Prague 7, Czech
Republic
Tel: 420-266-782040
Fax: 420-266-782990

USA & Canada

16 Goodyear, Suite 120, Irvine, CA 92618
Tel: 1-949-7539640
Fax: 1-949-7539020