

Switch

8-Port 10/100/1000

GS-7308

8-Port Gigabit Ethernet Switch



The GS-7308 is a Gigabit Ethernet desktop switch designed for small office or home office applications. It provides Eight 10/100/1000 Mbps auto-negotiation ports and supports auto-MDI/MDIX. The ports can be used to connect to a PC or Server as well as uplink ports to connect other network devices. With the GS-7308, users can keep their original 100 Mbps network cabling in place and, if supported by network devices, increase transmission rate by replacing it with a Gigabit Switch. The GS-7308 supports automatically shifting to power-saving mode when ports are not in use.

FEATURES

- Eight 10/100/1000 Mbps auto-negotiation Ethernet ports.
- Complies with IEEE802.3, IEEE802.3u, IEEE802.3ab Ethernet standards.
- Supports auto MDI/MDIX.
- Supports IEEE802.3x full duplex flow control, half duplex (Backpressure) flow control.
- · Power saving design when ports are inactive.
- · Integrated 8K MAC address table.
- Non-blocking.
- Store-and-forward switching.

www.comtrend.com

GS-7308

8-Port 10/100/1000

| Chipset Solution | DTI 2272N 00 |
|-----------------------------------|--|
| Standards | RTL8370N-CG |
| Standards | IEEE802.3 10Base-T Ethernet |
| | IEEE802.3u 100 Base-TX Fast Ethernet |
| | IEEE802.3ab Gigabit Ethernet |
| Case | |
| | Plastic |
| Interface and Speed | |
| | 8 RJ-45 ports and 10/100/1000Mbps per port |
| Functions | |
| | auto-MDI/MDIX, Storm-Protection |
| Transmission Method | |
| | store-and-forward |
| MAC Address Table | |
| D 1 E | 8K entries |
| Packet Filtering/ Forwarding Rate | 44000 (4018) |
| | 14880pps(10Mbps)per port |
| | 148800pps(100Mbps) per port 1488000pps(1000Mbps) per port |
| MAC Address Learning | 1400000pps(1000ivibps) per port |
| MAO Address Ecanning | Self-learning, auto-aging |
| Power | Och-learning, auto-aging |
| | External power supply 5V/1A |
| Power Consumption | |
| <u>'</u> | 3.482W |
| Operating Temperature | |
| | 0°C ~ 40°C |
| Storage Temperature | |
| | -40℃ ~ 70℃ |
| Operating Humidity | |
| | 10%~90% RH no condensing |
| COMTREND | |

Comtrend | 14 Chrysler, Irvine, CA 92618, USA | Tel: 1-949-753-9640 | Fax: 1-949-753-9020 | www.comtrend.com