

PoE Switch

18-Port Ethernet Switch [16 PoE Ports + 2 Combo Gigabit Ports]

GS-7518

Deliver data and power together to your network devices.

The GS-7518 is equipped with 16 Gigabit ports, as well as two Gigabit Ethernet Combo ports. It is designed for medium or large network environment to strengthen its network connection, specifically connecting to WiFi Access Point and IP surveillance cameras. The GS-7518 supplies a 240 watt power budget for PoE function, each Ethernet port is compliant with the IEEE 802.3af & IEEE 802.3at standards.



FEATURES

- 16 Gigabit Ethernet PoE LAN + 2 Gigabit Ethernet/SFP combo ports
- PoE Standards: IEEE 802.3af / IEEE 802.3at
- PoE Capable Ports: Ports 1-16
- PoE output power capacity: Maximum output: 30 watts per port, 240 watts total power budget
- Wall mount bracket included

Specification

Standards

IEEE802.3 10BASE-T
IEEE802.3u 100BASE-TX
IEEE802.3ab 1000BASE-T
IEEE802.3az EEE
IEEE802.3at, IEEE802.3af

Features

GbE ports (RJ45): 16
GbE combo ports (RJ45 + SFP): 2
MAC address Table: 8K
Packet buffer size: 4.1M
Jumbo Frame: 9K bytes

Power Requirement

100~240V/AC, 50~60Hz

PoE Power Budget

240 Watts

Dimensions

441(W) x 196(D) x 44(H) mm

Fan Design

Fan*2 with Fan Tray

Temperature

Operating: 0 ~ 40°C
Storage : -40 ~ 70°C

Humidity

Operating: 10% ~ 90% RH (non-condensing)
Storage : 5% ~ 90% RH (non-condensing)

Certifications

FCC Class A, CE



COMTREND CORPORATION

Taiwan:

3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanchong Dist, New Taipei City 24159, Taiwan
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

USA & Canada:

14 Chrysler, Irvine CA 92618, USA
Tel: 1-949-7539640
Fax: 1-949-7539020

Spain:

Edif. América II C/Prócion,7 portal 3 bajo H 28023
Madrid, Spain
Tel: 34-917990403
Fax: 34-913510999

Czech Republic:

TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990