

COMPACT VANDAL DOME | IP CAMERA



PRODUCT OVERVIEW

Compact design for the ultimate versatility. Comtrend's VD21IR Compact Vandal Dome IP Camera offers a sleek compact design for indoor areas, and remains durable with vandal and weather proof certified housing for outdoor areas. It supports 3-axis (pan, tilt and lens module) manual rotation for easy adjustments for the proper viewing site, and with built-in IR LEDs the VD21IR supports day/night function even in an environment with no light.

KEY BENEFITS

Sleek Compact Design

Easily hidden and subtle for minimal impact to the environment.

Built-In IR LED

Supports day/night function even in an environment with no light.


Supports Multiple Video Streams

Can simultaneously stream H.264, MPEG-4, and MJPEG

Vandal & Weather Proof

Vandal proof IK8 and weather proof IP66 certified casing.

MB-21IR



3 Axis Rotation!

FEATURES

- Multi-stream from H.264/MPEG-4/MJPEG
- 30 fps @ 1920x1080
- Built-in 3.6mm, IR mega lens
- Supports two-way audio
- IR illuminators, effective up to 65 feet
- Built-in MicroSD card slot(32GB max)
- Vandal proof IK8
- Weather proof IP66
- Supports iOS and Android
- PoE Power (IEEE802.3af)

SPECIFICATIONS

System

CPU: TI Multimedia SoC
Flash/RAM: 32MB/128MB

Image Sensor

Max. Resolution: 1920 (H) x 1080(V)
Format: 1/2.5"

Effective Pixels: 2056 (H) x 1536(V)

Lens

Focal Length: f=3.6mm
Iris (F No.): F1.8
Angle of View H: 69°; V:37°; D:75°

Day & Night

Mechanical IRCF(ICR): Yes (Built-in Removable IR-cut filter)
IR Distance (Max.): 65ft., 850nm

Min. Illuminators

Color Mode: 0.05 Lux
B/W Mode: 0 Lux (IR On)

Video Codec

H.264: 30fps @ 1920 X 1080 (Max. 1080P)
MPEG-4: 20fps @ 1920 x 1080 (Mac. 1080P)
MJPEG: 30fps @ 720 x 480 (Max. D1)

Interface

Local Storage: MicroSD Slot (Support Max 32GB)
Digital In/Digital Out: Digital Input/Digital Output
RS-485: RS-485x1, Support Pelco-D/Custom
Audio in/out: Two-way, Supports G.711 μ-Law RCA-In x 1 / RCA-Out x 1 (3.5mm)
Network: Fast Ethernet (10/100Mbps, RH-45 port)
Reset Button: Push Button

Protocols

IPv4, Ipv6, TCP/IP, UDP, HTTP, HTTPS, RTP, RTSP, RTCP
ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, PPPoE, QoS
ToS, DSCP, UPnP, Samba, Bonjour

Power Supply

PoE/DC Power: PoE (IEEE802.3af)
Power Consumption: PoE, Max. 6.6W/DC 12V, Max. 4.3W

Mechanical Spec

Dimensions, Weight: 4.3in. (Ø) x 3.15in. (H), Net 11oz.
Pan-n-Tilt: Pan: 350°; Tilt: 30-90°
Weatherproof: IP66
Vandal Proof: IK8

Special Features

Motion Detection: 3 Scalable Windows
Privacy Mask: 3 Scalable Windows
Recording Options: Remote Client, MicroSD Card or Remote Samba Recording
Exposure Management: Full View/ BLC (Metering Area), AWB, AES, AGC
Image Settings: Brightness, Contrast, Sharpness, Saturation Adjustable
Shutter Time: Auto/Menu Mode
1/15-1/25000sec (Image Sensor) 1/15-1/10000sec (Menu Mode)
Mirror: Vertical, Horizontal
Onvif Compliant: Supports Onvif Profile S
Digital Zoom: Up to 10x Digital Zoom
Network Management: IP Filter, QoS (DSCP)
Time Management: Manual Time Setting, Time Server & NTP Support, Real Time Clock
User Access Control: Multi-Level User Access, Up to 5 Clients
Multiple Streaming: Max. 3 Streams
Configuration File: Backup to PC/ Backup to SD Card
Web Browser: Internet Explorer 9.x above
Operating System: Suggest Windows 7/8/8.1 above
Language: Supports multiple languages

Event and Alarm Operation

Alarm Trigger: Video Motion Detection, Digital Input (Always/Schedule setting)
Event Action: FTP, Email, SD Card Rec., NAS Rec., Digital Output
One Snapshot/Rec. Video File
Alarm Rec. Buffer: 5 sec Pre-alarm/ 5 sec post-alarm, Up to 3MB

Accessory

Recording Software: 64-CH VMS Software
Installation Guide: Quick Installation Guide, Manual CD
Kit: Screw Kit

Certificate & Warranty

CE class A, FCC class A
2 Year Warranty