

GPON ONT

GPON | 1x Gigabit Ethernet | TR-069

GRG-4284



GRG-4284 is a next-generation Gigabit Passive Optical Network (GPON) ONT, ideal for Fiber to The Home solution designed for advanced triple-play deployments. It's an incredibly robust device allowing users to access a high-speed internet connection via its GPON port and share it with a Gigabit Ethernet port.

The indoor models of Comtrend's GPON product line provide a lower cost and small package which contains many features including QoS, Data Bridge and multicast video support.

Compliant with standard OMCI definition, GRG-4284 is manageable from the remote side and supports the full range of FCAPS functions including supervision, monitoring and maintenance.

KEY FEATURES

- **Access to Fiber Optical Network:** Supports downstream 2.5Gbps and upstream to 1.25Gbps with a transmission distance of up to 20km.
- **Easy Remote Management:**
 - GRG-4284 supports the ONT Management and Control Interface (OMCI), making it easy to configure, activate and manage remotely from an Optical Line Terminal (OLT).
 - TR-069 standard data model for ISP remote control.

GRG-4284

GPON | 1x Gigabit Ethernet | TR-069

SPECIFICATIONS

| HARDWARE | |
|---|---|
| Flash | NOR Flash: 16M Bytes |
| RAM | DDR: 64M Bytes |
| Interfaces | 1x GPON (SC/APC) 1x Gigabit Ethernet LAN |
| LED Indicators | Power, LOS, PON, LAN |
| Buttons | Reset button |
| Power Input | 12VDC/0.5A |
| SOFTWARE | |
| Quality of Service | WMM, Bandwidth Control |
| Port Forwarding | L2/L3 forwarding, L3 NAT |
| VPN | 802.1Q tag VLAN, VLAN transparent mode/VLAN translation mode/VLAN trunk mode |
| Access Control | Local Management Control, Host List, Access Schedule, Rule Management |
| Firewall Security | DoS, SPI Firewall, IP Address Filter/MAC Address Filter/Domain Filter, IP and MAC Address Binding |
| Management | Access Control, Local Management, Remote Management |
| REMOTE MANAGEMENT | |
| Protocol | TR-069, OMCI, HTTP, HTTPS, TELNET, SSH |
| CERTIFICATIONS | |
| CE, RoHS | |
| PACKAGE CONTENTS | |
| GPON ONT (GRG-4284) | |
| Power adapter 12VDC/0.5A, 100-240VAC, 50/60Hz, 1.5m | |
| ENVIRONMENT | |
| Temperature | Operating: 0°C ~ 40°C (32°F ~104°F) Storage: -40°C ~ 70°C (-40°F ~158°F) |
| Humidity (Non-condensing) | Operating: 10 ~ 90% RH, non-condensing Storage: 5 ~ 90% RH, non-condensing |



Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanzhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
C/ Proción, 7 portal 2, 1º C - Edif. América II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.