

XGS-PON WiFi 7 GW BE7200

2.4GHz & 5GHz 4x4 Concurrent | 10GE LAN | VoIP | USB

GRG-4355u



Comtrend's **GRG-4355u** is designed as an XGS-PON device. It offers high-performance Data, Voice and Video services for individual users, SOHO (small office or home office) setups, and small businesses, among others.

It provides one high-speed 10GE LAN port and four GE ports, along with two FXS ports for internet calling. It also features dual-band Wi-Fi 7 (4T4R 802.11be@2.4GHz and 4T4R 802.11be@5GHz). The two wireless bands are separated into two dedicated Wi-Fi networks, which support more end-user devices while reducing signal interference. Furthermore, there is a USB 3.0 host interface on the user side.

KEY FEATURES

- **Dual-band MLO in Wi-Fi 7:** Simultaneous Multi-Link Operation on two frequency bands amplifies throughput, improves reliability, optimizes load balancing, and reduces latency by dynamically utilizing spectrum resources
- **OFDMA and MU-MIMO:** Supports both up-link and down-link, allowing efficient data transmission for more devices at the same time
- **XGS-PON: 10G/10G UL/DL** provides high speed fiber to the home services
- **4x 10/100/1000BASE-T** Ethernet LAN ports
- **1x 10GE** Ethernet LAN port
- Supports **Voice over Internet Protocol** (VoIP) as a flexible and affordable solution for voice calls
- **1x USB3.0**
- **Remote Management:** TR-069 standard data model for ISP remote control

GRG-4355U

2.4GHz & 5GHz 4x4 Concurrent | 10GE LAN | VoIP | USB



SPECIFICATIONS

Flash Memory	512MB	
SDRAM	512MB	
WAN(PON)	1 x XGS-PON SC/APC Both downstream and upstream rates can reach 10Gbps	
10G LAN	1x RJ-45 Port	
GE LAN	4x RJ-45 Ports	
FXS (VoIP)	2x RJ-11 Ports	
USB	1x USB3.0	
Buttons	Power, WPS, Factory Reset	
LEDs	POWER / PON / LOS / NET / 2.4G/5G / lan1~4 / TEL1~2	
Features	WAN Type: IPoE / Static IP / PPPoE / Bridge Supports VLAN 1-4094 Protocols: IPv4 / IPv6 dual stack Support IGMP Snooping & Proxy T.30/T.38/G.711 FAX mode Supports WAN/LAN access the Telnet & HTTP Supports Parental Controls Security: Firewall, IP/ MAC /URL Filter Supports TR-069 Remote Management Protocol Call waiting/ Unconditional Call Forward/Call Forward Busy/ Call Forward No Reply/ Three-party calls	
WiFi	2.4GHz: 11be 4x4 2.4G Phy rate: 1376Mbps	5GHz: 11be 4x4 5G Phy rate: 5764Mbps
Power Adaptor	DC 12V/3A	
Dimensions	190mm x 80mm x 255mm (L x W x H)	
Certifications	CE & RoHS	

ENVIRONMENT

Operating Temperature	0~45 degrees Celsius
Operating Humidity	5~95%

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanchong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100 Irvine,
CA 92618 USA
Tel: +1-949-753-9640

Spain:
comercial@comtrend.com

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040

India:
446 Sector 8, IMT Manesar, Gurugram,
Haryana 122051, India
E-mail: India.admin@comtrend.com

Product specifications and design are subject to change without notice.