

xDSL Bonding Gateway

Multi-DSL Bonding | GE LAN | TR-069

NexusLink 3130



NexusLink 3130 is a Multi-DSL Bonding Gateway that not only provides both ADSL and VDSL but also supports xDSL bonding for extending WAN access bandwidth. Additionally, it supports VDSL 35b profile on single line providing even higher speeds on existing VDSL2 networks.

The device complies with TR-069/TR-098/ and TR-111 standards to ensure interoperability with standards-based software and hardware. NexusLink 3130 is designed for high-speed applications and is suitable for triple play services. Installation is straightforward and the device provides all the functions necessary to create a secure and high-speed Internet connection.

KEY FEATURES

- **VDSL Bonding:** A technology that combines 2 standard VDSL2 lines into a single virtual connection that allows ISPs to double the bitrate/speed of their existing customers' connection.
- **Future-Proof with A/VDSL:** Offers VDSL2 with ADSL2+ fallback for flexible future transitional deployments.
- **Provides Optimized Performance:** Supports the latest G.vector & G.inp technologies to work together to mitigate crosstalk and impulse noise resulting in greater throughput.
- **Supervectoring:** Part of next-generation broadband technologies - with more frequency ranges than ever before, you can achieve even greater bandwidth (up to 300 Mbit/s download, up to 50 Mbit/s upload).
- **Remote Management for Reduced Truck Rolls:** Supports TR-069 to easily setup, manage, troubleshoot and control the CPE remotely.

NexusLink 3130

Multi-DSL Bonding | GE LAN | TR-069

SPECIFICATIONS	
Hardware	<ul style="list-style-type: none">▪ 1x RJ-14 for 35b VDSL single line▪ 17a VDSL2 bonding▪ ADSL2+ (Annex A) bonding▪ 1x Gigabit Ethernet LAN▪ 1x Reset button▪ 1x Power switch
ADSL	<ul style="list-style-type: none">▪ G.994▪ G.992.1 (G.dmt) Annex A▪ G.992.2 (G.lite) Annex A▪ ANSI T1.413▪ G.992.3 (ADSL2) Annex A▪ G.992.5 (ADSL2+) Annex A
VDSL	<ul style="list-style-type: none">▪ G.993.2(VDSL2) 35b, 30a, 17a, 12a, 12b, 8a, 8b, 8c, 8d▪ G.993.5 (G.vector)▪ G.998.4 (G.INP)▪ SRA (Seamless Rate Adaptation)▪ UPBO (Upstream Power Back-off)
Ethernet	<ul style="list-style-type: none">▪ IEEE 802.3, IEEE 802.3u IEEE 802.3ab▪ 10/100 /1000 BASE-T, auto-sense▪ Supports MDI/MDX
Networking Protocols	<ul style="list-style-type: none">▪ RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Router, RFC 2516 (PPPoE); RFC 1577 (IPoA)▪ PPPoE Pass-Through, Multiple PPPoE Sessions on Single WAN Interface▪ PPPoE Filtering of Non-PPPoE Packets Between WAN and LAN▪ Transparent Bridging Between all LAN and WAN Interfaces▪ 802.1p/802.1q VLAN, DSCP▪ IGMP Proxy V1/V2/V3, IGMP Snooping V1/V2/V3, Fast leave▪ Static route, RIP v1/v2, ARP, RARP, SNTP▪ DHCP Server/Client/Relay, DNS Proxy/ Relay, Dynamic DNS, UPnP, DLNA▪ IPv6 Dual Stack, IPV6 Rapid Deployment (6RD)
Management	<ul style="list-style-type: none">▪ TR-069/TR-098/TR-104/TR-111/TR-181, SNMP, Telnet, Web-Based Management, Configuration Backup and Restoration▪ Software Upgrade via HTTP, TFTP Server, or FTP Server
Firewall/Filtering	<ul style="list-style-type: none">▪ Stateful Packet Inspection Firewall▪ Stateless Packet Filter▪ URI/URL Filtering▪ Denial of Service (DOS): ARP Attacks, Ping Attacks, Ping of Death, LAND, SYNC, Smurf, Unreachable, Teardrop▪ Port Scan Detection and Protection▪ TCP/IP/Port/Interface Filtering Rules Support Both Incoming and Outgoing Filtering
NAT/PAT	<ul style="list-style-type: none">▪ Support One to One, Many to One, Many to Many (Overload), Many to Many (No Overload) NAT▪ NAT Loopback▪ Port Triggering▪ Port Forwarding (Virtual Server)▪ Symmetric port-overloading NAT, Full-Cone NAT▪ DMZ host▪ VPN Pass Through (PPTP, L2TP, IPSec)

NexusLink 3130

Multi-DSL Bonding | GE LAN | TR-069

SPECIFICATIONS

Power Supply	<ul style="list-style-type: none">External power adapter: 12VDC/ 1.5A
Dimensions	<ul style="list-style-type: none">171 x 122 x 38mm (WxDxH)
Weight	<ul style="list-style-type: none">0.6 kg

PACKAGE CONTENTS

xDSL Bonding Gateway (NL-3130)

Power adapter 12VDC/1.5A, 110-220VAC, 50/60Hz

ENVIRONMENT

Operating Temperature	0°C ~40°C (32°F ~104°F)
Operating Humidity	10%~90% non-condensing
Storage Temperature	-25°C ~65°C (-13°F ~149°F)
Storage Humidity	5%~90% non-condensing



Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanzhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
C/ Proción, 7 portal 2, 1º C - Edif. América II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-762040