

Wireless Gigabit VoIP Router AC1200

1 GE WAN | 4 GE LAN | 1 FXS | 1 USB | 2.4G 2T2R 5G 2T2R

VG-8026u



The **VG-8026u** creates a reliable and blazing-fast network powered by 802.11ac Wi-Fi technology. The 2.4GHz band delivers speeds up to 300Mbps, ready for everyday tasks like emailing and web browsing, while the 5GHz band delivers speeds up to 867Mbps, ideal for HD video streaming and lag-free online gaming.

The VG-8026u is a powerful network hub providing one gigabit WAN port and four gigabit LAN ports. Wired speeds can be up to 10 times faster than standard fast Ethernet ports. It unlocks the potential of your home network when broadband access is over 200M.

KEY FEATURES

- **Versatile USB Connectivity**
A USB 2.0 port makes the VG-8026u a truly resourceful gateway. Share a hard drive full of media through your home network, or via an ftp server whenever you're away.
- **Supports VoIP Calls**
With an FXS port, users can make or receive phone calls over the Internet simply by connecting the device to their existing telephone set.
- **Better networking experience without interference**
The VG-8026u supports various advanced features, including Parental Control, Guest Network and QoS, to guarantee a fast, stable and secure online experience, freeing you from the disturbance of buffering and threats of network attacks.

VG-8026u

1 GE WAN | 4 GE LAN | 1 FXS | 1 USB | 2.4G 2T2R 5G 2T2R

SPECIFICATIONS

Hardware	<ul style="list-style-type: none">▪ Interfaces: 1x 10/100/1000Mbps WAN Port, 4x 10/100/1000Mbps LAN Ports, 1x FXS Port, 1x USB2.0 Port▪ Buttons: Power ON/OFF Button, WPS Button, WiFi Button, Reset Button▪ Power Supply: DC 12V 1.5A▪ Antenna: 2x2dBi dual band internal antennas + 1x2dBi 2.4G internal antennas▪ Dimensions (WxDxH): 210 x 150 x 32mm
General	<ul style="list-style-type: none">▪ VoIP Standards: SIP (RFC3261), ITU-T G.729/G.722/G.711a/G.711
Software Features	<ul style="list-style-type: none">▪ WAN Type: Dynamic IP/Static IP/PPPoE▪ DHCP: Server, Client, DHCP Client List, Address Reservation▪ Quality of Service: WMM, Bandwidth Control▪ Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ▪ VPN: PPTP, L2TP, IPSec▪ Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management▪ Firewall Security: DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding▪ USB Sharing: Supports Samba(Storage), FTP Server, Media Server, Printer Server, DLNA▪ VoIP Features: One RJ-11 FXS port for connecting to analog telephones Call forwarding, Call waiting, Call block, 3-way conference call, etc.▪ Management: Access Control, Local Management, Remote Management▪ Internet Protocol: IPv4, IPv6
ENVIRONMENT	
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Relative Humidity	10%~90%, non-condensing
Storage Humidity	5%~90%, non-condensing



Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanzhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100 Irvine,
CA 92618 USA
Tel: +1-949-753-9640

Spain:
C/ Proción, 7 portal 2, 1º C - Edif. América II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040