

xDSL Gateway

A / VDSL | GE LAN

VR-3046



Comtrend's VR-3046 is designed as a multi-DSL gateway that provides wired access for high-bandwidth applications in the home or office. It includes one Gigabit Ethernet port and supports ADSL2/2+ and VDSL2 connections with automatic fallback to ADSL2+.

The VR-3046 supports routed or bridged mode and up to profile 35b in VDSL2 mode for 100Mbps upstream and 300Mbps downstream high-speed bandwidth. On longer loops, VDSL2 35b falls back to VDSL2 17a vectoring performance. The device can satisfy online gaming, video streaming, and real-time audio applications. Furthermore, installation is simple and straightforward.

KEY FEATURES

- **Future-Proof with A/VDSL:** Offers VDSL2 with ADSL2+ fallback for flexible future transitional deployments.
- **Provides Optimized Performance:** Supports the latest G.vector & G.inp technologies to work together to mitigate crosstalk and impulse noise, resulting in greater throughput.
- **Supervectoring:** Part of next-generation broadband technologies - with more frequency ranges than ever before, you can achieve even greater bandwidth (up to 300 Mbit/s download, up to 50 Mbit/s upload).
- **Quality of Service:** Classifies, controls and prioritizes diverse traffic types, for pristine video, toll-quality voice, and error free data transmissions.
- **Remote Management for Reduced Truck Rolls:** Supports TR-069 to easily setup, manage, troubleshoot and control the CPE remotely.

VR-3046

A / VDSL | GE LAN

SPECIFICATIONS

HARDWARE

Flash	NAND Flash: 128M Bytes
RAM	DDR2: 128M Bytes
Interfaces	1x A / VDSL (35b) 1x Gigabit Ethernet LAN
LED Indicators	Power, GE, DSL, Internet
Buttons	Power Switch, Reset button
Power Input	12DVC/1A, 100-240ACV, 50/60Hz

SOFTWARE FEATURES

Safe & Secure Connections	Stateful Firewall (with DoS protection) and NAT/PAT
Management Function	TR-069, HTTP, HTTPS, TELNET, SSH

PACKAGE CONTENTS

xDSL Gateway (VR-3046)
Power adapter 12VDC/1A, 110-220VAC, 50/60Hz

ENVIRONMENT

Temperature	Operating: 0°C ~ 40°C (32°F ~104°F) Storage: -40°C ~ 70°C (-40°F ~158°F)
Humidity (Non-condensing)	Operating: 10 ~ 90% RH, non-condensing Storage: 5 ~ 90% RH, non-condensing

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanxhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29998261

USA & Canada:
530 Technology Dr. Suite 100, Irvine,
CA 92618, USA
Tel: +1-949-753-9640

Spain:
comercial@comtrend.com

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040

India:
446 Sector 8, IMT Manesar, Gurugram,
Haryana 122051, India
E-mail: India.admin@comtrend.com

Maximum performance, actual data rates, and coverage will vary depending on network conditions and environmental factors. Product specifications and design are subject to change without notice.