

xDSL/Eth Gateway AC1200

GE LAN | GE WAN | 2.4G 2T2R + 5G 2T2R | USB 2.0

VR-3047eu



The **VR-3047eu** makes full use of its dual-band Wi-Fi abilities, reaching speeds of up to 300Mbps on the 2.4GHz band and 867Mbps on the 5GHz band. Enjoy a total speed of up to 1200Mbps to eliminate buffering from your HD streams and lag from online games. The two wireless bands are separated into two dedicated Wi-Fi networks, supporting more devices while reducing signal interference.

The core design concept of VR-3047eu is to enhance user experience on high speed applications by providing better coverage and stable Wi-Fi services.

KEY FEATURES

- **Satisfies Multiple Needs in one Device:** The modem router combines the function of VDSL modem, NAT router, 4-port switch and wireless access point into one fashionable device, providing a one-stop solution for your home network connection.
- **Full Gigabit Wired Connections for Ultrafast Data Transfer Speeds:** With one Gigabit WAN port and four Gigabit LAN ports, speeds can be up to 10x faster than standard Ethernet connections.
- **Maximizes Video Streaming:** Equipped with 802.11ac Wave 2 technology, deliver super-charged 2x2 AC1200, MU-MIMO wireless connectivity to enhance video experience.
- **Provides Optimized Performance:** Supports the latest G.vector & G.inp technologies to work together to mitigate crosstalk and impulse noise, resulting in greater throughput.
- **Versatile USB Sharing:** With the USB 2.0 port, you can share printers, files, and media with various devices on your local network or via FTP server.

VR-3047eu

GE LAN | GE WAN | 2.4G 2T2R + 5G 2T2R | USB 2.0

SPECIFICATIONS	
Hardware	<ul style="list-style-type: none">▪ Interfaces: 1x 35b VDSL /ADSL2+, 1x Gigabit Ethernet WAN, 4x Gigabit Ethernet LAN, 1x USB 2.0▪ Power Supply: DC 12V 1.5A▪ Memory: 16MB FLASH / 128MB DRAM (embedded)▪ Antenna: 4x internal antennas▪ Dimensions (WxDxH): 186x151x30mm
General	<ul style="list-style-type: none">▪ DSL Standards: VDSL2, ADSL2/2+, ADSL (Annex B)▪ Supports VDSL2 8a,8b,8c,8d,12a,12b,17a,35b profile▪ Wireless Standards: IEEE802.11a/n/ac,5GHz, IEEE802.11b/g/n, 2.4GHz▪ Signal Rate: 5GHz: Up to 876Mbps, 2.4GHz: Up to 300Mbps▪ Wireless Security: WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption
Software Features	<ul style="list-style-type: none">▪ WAN Type: ATM/PTM/ETH/Dongle▪ DHCP: Server, Client, DHCP Client List, Address Reservation▪ Quality of Service: WMM, Bandwidth Control▪ Port Forwarding: Virtual Server, Port Triggering, UPnP, DMZ▪ VPN Pass-Through: PPTP, L2TP, IPSec▪ Access Control: Parental Control, Local Management Control, Host List, Access Schedule, Rule Management▪ Firewall Security: DoS, SPI Firewall, IP Address Filter / MAC Address Filter / Domain Filter, IP and MAC Address Binding▪ USB Sharing: Support Samba (Storage) / FTP Server, Media Server / Printer Server / DLNA▪ Management: Access Control, Local Management, Remote Management▪ Internet Protocol: IPv4, IPv6
PACKAGE CONTENTS	
xDSL/Eth Gateway (VR-3047eu)	
Power adapter 12VDC/1.5A 100-240VAC, 50/60/Hz	
ENVIRONMENT	
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Relative Humidity	10%~90%, non-condensing
Storage Humidity	5%~90%, non-condensing

COMTREND

Taiwan:
3F-1, No.10, Lane 609, Chongxin Road, Section 5,
Sanzhong Dist, New Taipei City 241405, Taiwan
Tel: +886-2-29988261

USA & Canada:
530 Technology Dr, Suite 100 Irvine,
CA 92618 USA
Tel: +1-949-753-9640

Spain:
C/ Proción, 7 portal 2, 1º C - Edif. América II
28023 Madrid, Spain
Tel: 34-917990403

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7,
Czech Republic
Tel: +420-266-782040